

## OZZ XBI LED light-bar with dual color positionslys, E-approved

E-approved LED lightbars with dual position-light that allows you to switch between white and yellow position-light. Choose between P9" and P20".



Super nice LED lightbars from OZZ with dual position-light, that sit on the top of the lamp without any visible LED's. That gives you the possibility to change between white and yellow positions-light as you feel like it so that it fits your vehicle.

The lightbars are available as P9" (42W) and P20" (120W). These lightbars are ECE-approved so that you can use them on public roads. They can advantageously replace the classic halogen long-beams. When starting up the light bars the chosen position light will light up in a very cool animation.

In regards to the light diagram, it shows 1 lux at 315m (P9") and 590m (P20") respectively. You will, therefore, get more light than the diagram shows and be able to see the reflections in the cones on the side of the road further out.

The lens glass is produced in polycarbonate and the lamp housing is made of powder-coated aluminum to achieve a sleek design and good cooling for the LEDs.

The supplied brackets are manufactured in black aluminum. The lightbars also come with a suitable DT Deutsch-plug, which makes the installation much easier.

- Black: -
- Red: High-beam
- White: White position-light
- Yellow: Yellow position-light

matronics 

Buy online at [www.matronics.eu/24606485](http://www.matronics.eu/24606485)

## Product overview

### P9" (42W) - 4960 Lumen



SKU 24606485  
Voltage: 10-32V DC  
Consumption: 42W  
Lumen theoretical: 4960lm  
Lumen effective: 3100lm  
Reference value: 27,5  
Kelvin: 5000K  
Warranty: 3 years  
Operating temperature: - 40°C to +60°C  
Dimensions: 70 x 50 x 228mm

### P20" (120W) - 11200 Lumen



SKU 24606486  
Voltage: 10-32V DC  
Consumption: 120W  
Lumen theoretical: 11200lm  
Lumen effective: 7000lm  
Reference value: 50  
Kelvin: 5000K  
Warranty: 3 years  
Operating temperature: - 40°C to +60°C  
Dimensions: 80.9 x 50.3 x 544mm