## LED Stripes, Splashproof, 5m - I2V

5 metres splashproof LED SMD stripe with a bright light. 350-950 Lumen per m.



The splashproof LED Tape SMD can be shortened or extended further, so it fits for your project. The stripe is 8/10 mm wide and is built up in small modules of 5 cm or 10 cm, where there are 3-6 heavy SMD diodes in a circuit ready for 12Vdc. There are clear markers where the stripe can be cut, as well as solder-islands, where you can solder wire on or extend with more SMD-tape. On the back is a 3 m powerful tape, which makes that LED SMD tape to stay attached to his seat without screws.

It is sold in coils of 5 metres, but you can short it up/prolong it, so that it fits for the task. They should not be used in particularly exposed areas with water (for example aquarium lighting), as the product is only splashproof.

The solid color SMD LED stripe can be connected directly to 12Vdc or to a 12Vdc transformer, which can be purchased from us as well. The LED stripe can also be attenuated in the brightness via our 12Vdc dimmers, which are mounted between the tape and the transformer.

The installation is very simple, but it must be used in houses/buildings and according to the law - should be mounted by an electrician.

# matronics.

Buy online at www.matronics.eu/609040

#### Product overview

#### Warm white, 350 Lumens



SKU 609040 Voltage: DC12V Watt / m: 4.2 Watt LEDs / meter: 60

Color temperatur: 3200 Kelvin

#### Warm white, 700 Lumen



SKU 609148 Voltage: DC12V Watt / m: 8.4 Watt LEDs / meter: 120

Color temperatur: 3200 Kelvin

#### Warm white, 1600 Lumen



SKU 609141 Voltage: DC12V Watt / m: 12.0 Watt LEDs / meter: 120

Color temperatur: 3000 Kelvin

#### Neutral white, 1600 Lumen



SKU 609142 Voltage: DC12V Watt / m: 12.0 Watt LEDs / meter: 120

Color temperatur: 4000 Kelvin

### Cool white, 360 Lumens



SKU 609041

Light output per 100 cm: 360 Lumen

Diodes per meter: 60stk

Light Scattering: 120 ~ 140 degrees

LED Type: 1210 SMD Voltage: 12Vdc Tracking: 5 cm

Color: Cool White ~ 6500 k Consumption per coil: 21,0 Watt ~

1750mA

Colour Rendering (Ra): 75

Consumption per metre: 4.2 Watts ~ 350mA

Density: IP54 Bandwidth: 8 mm Voltage: DC12V Watt / m: 4.2 Watt

LEDs / meter: 60

Color temperatur: 6500 Kelvin

## Cool white, 700 lumen



SKU 609149 Voltage: DC12V Watt / m: 8.4 Watt LEDs / meter: 120

Color temperatur: 6000 Kelvin

### Red, 680 lumen



SKU 609151 Voltage: DC12V Watt / m: 8.4 Watt LEDs / meter: 120

#### Green, 270 Lumens



SKU 609034 Voltage: DC12V Watt / m: 4.2 Watt LEDs / meter: 60

## Green, 860 lumen



SKU 609152 Voltage: DC12V Watt / m: 8.4 Watt LEDs / meter: 120

## Blà, 360 lumen



SKU 609150 Voltage: DC12V Watt / m: 8.4 Watt LEDs / meter: 120

#### Yellow, 80 Lumens



SKU 609035 Voltage: DC12V Watt / m: 4.2 Watt LEDs / meter: 60

## Accessori, Rubber-bracket 8mm



SKU 609298

# Accessori, Rubber-bracket IOmm



SKU 609299

# Product pictures





















