5 pcs. 3 mm LEDs for External I2V

5 waterproof diodes ready for mounting with 1.0 m cable and mounting frames.



5 waterproof diodes ready for mounting with 1.0 m cable and mounting frames. They are typically used for power lighting, license plate lights or endoutline marker lamps, since they have a wide light scattering.

The cable length is 1.0 m. The mounting hole should be 6,5 mm. It can also be attached via cable stripes and a stripes-anchor.

matronics.1

Buy online at www.matronics.eu/120002

Product overview

Blue



SKU 120002 Light Scattering: 120 ° Color: Blue Brightness: 1000mCD Lens type: Diffuse Operation Voltage: 12V @ 20mA Wave Length: ~ 470nm





SKU 120012 Light Scattering: 120 ° Lens type: Clear glass Color: Red Brightness: 1000mCD Operation Voltage: 12V @ 20mA Wave Length: ~ 470nm

Green



SKU 120032 Light Scattering: 120 ° Color: Green Lens type: Diffuse Brightness: 1300 mcd Wave Length: ~ 525nm Operation Voltage: 12V @ 20mA

Warm-white



SKU 120056 Lens type: Clear glass Operation Voltage: 12V @ 20mA Light Scattering: 60 ° Color: Warm white 2700 k Brightness: 6000 mcd

Xenon white



SKU 120052 Color: White 6500 k Operation Voltage: 12V @ 20mA Lens type: Diffuse Brightness: 1000 mcd Light Scattering: 120 °

Yellow



SKU 120022 Brightness: 1000mCD Light Scattering: 120 ° Color: Yellow Lens type: Diffuse Wave Length: ~ 589nm Operation Voltage: 12V @ 20mA

Orange



SKU 120042 Operation Voltage: 12V @ 20mA Brightness: 1000 mcd Lens type: Diffuse Wave Length: ~ 605nm Light Scattering: 120 ° Color: Orange

Product pictures

