

Cable, LIV 100m spool

Single wire for connections inside machines, enclosures and similar. 0.25mm2, 0.5mm2 and 1.5mm2 in 8 different colors



PVC single-core wire with for connections inside machines, enclosures and similar.

The wires are available as 0.25mm2, 0.5mm2 and 1.5mm2 in 8 different colors

Max peak voltage of 900V, and flexible operating temperature from -5 to 70 degrees, and fixed installation temperature from -30 to 80 degrees. This allows you to use this cable for any typical purpose.

The wires conform to the Low-Voltage Directive 2006/95/EG



Buy online at www.matronics.eu/509105-BK

Specifications

Sheath	PVC
Operating temperature, fixed	-30 to 80 degrees
Operating temperature, fleksibel	-5 to 70 degrees
Max peak voltage	900V

Product overview

0.25mm2, Sort



SKU 509105-BK

0.25mm2, Blue



SKU 509105-BL

0.25mm2, Brown



SKU 509105-BR

0.25mm2, Green



SKU 509105-GR

0.25mm2, Gray



SKU 509105-GY

0.25mm2, Red



SKU 509105-RD

0.25mm2, Yellow



SKU 509105-YL

0.25mm2, White



SKU 509105-WH

O.5mm2, Black



SKU 509110-BK

O.5mm2, Blue



SKU 509110-BL

O.5mm2, Brown



SKU 509110-BR

O.5mm2, Green



SKU 509110-GR

O.5mm2, Gray



SKU 509110-GY

O.5mm2, Red



SKU 509110-RD

O.5mm2, White



SKU 509110-WH

O.5mm2, Yellow



SKU 509110-YL

1.5mm2, Black



SKU 509115-BK

1.5mm2, Blue



SKU 509115-BL

1.5mm2, Brown



SKU 509115-BR

1.5mm2, Gray



SKU 509115-GY

1.5mm2, Red



SKU 509115-RD

1.5mm2, White



SKU 509115-WH

1.5mm2, Yellow



SKU 509115-YL

1.5mm2, Green



SKU 509115-GR

Product pictures

