Additional position light for Scania LED headlight 2016+

Special developed emitters that fits in to Scania +2016 LED headlights. A total of 30 bright LEDs completely lights up the reflector and front edge.



matronics.1

Buy online at www.matronics.eu/240877-AM

Matronics has developed these emitters especially for Scania +2016 with LED headlights. A total of 30 bright LEDs completely lights up the reflector, which creates a very special effect in an otherwise dark headlight. They are available with xenon white, yellow or warm white light.

They are a great addition to any Scania headlights, regardless if you have standard white, yellow or warm white DRL.

Single color, Yellow/White/Warm white

There is 3 meter wire on each emitter, that can be connected to the regular positionlight. There is a plus and minus wire.

Dual color

There is 3 meter cable on each board. There is one minus and two pluswires. You should never have both colors turned on, so you need to use a toggle switch to change between the colors.

Dual color + flash

Standard strobecolor is yellow, but it can be customized to eg. blue or white for special purpose vehicles.

There is 6 meter cable on the emitter with M8 connectors, that can be connected to the included controller. The controller manages the two colors, and automatically turn them off when you enable the strobe light. The controller itself has 3 meter wire. The cable has 4 wires:

- Minus Green cable
- Plus for white position light White cable
- Plus for yellow position light Yellow cable
- Plus for strobe light Brown cable

It is necessary to cut the cables with M8 connectors when mounting, so make sure you make the assembly waterproof, and connect the wires to the correct colors.

Mounting

Mounting them is easy, and the only permanent change in the headlight is a single hole, that is easily closed again. The emitters are mounted inside the headlight, and fastened with two existing screws.

There are two screws near the doors, that hold the headlights in place. They are loosened, where after the headlight can be swung to the side.

On top of the headlight is a large cap, that can be loosened and removed. Under the cap is a large heatsink.

The two front screws on the heatsink are loosened and removed.

Push the emitter sideways in to the headlight so that the two taps fits the holes in the heatsink. It is important that the emitter is placed above the reflector. You should not be able to see the emitter inside the headlight when it is mounted.

The two screws is fastened through the emitters in to the heatsinks.

We recommend that you drill a hole in the back plate of the light for feeding through the wire.

Product overview

Yellow



SKU 240877-AM

Xenon white



SKU 240877-CW

Golden yellow



SKU 240877-WW

SKU 240877-GY

Dual Color Amber / Xenon White



SKU 240877-DC

SKU 240910-AM

Dual Color Amber / Warm White



SKU 240877-AMWW

Dual Color Amber/ Warm white + Strobe

SKU 240910-WWAMAM





Product pictures





















