

Strands Siberia DR LED light-bar, E-approved

Strands double-rowed LED light-bar with dual colour position-light in the middle. E-approved for road use.









E-approved LED bars by Strands with dual-colour position-light in the middle making it a stylish and modern look. The LED bars are available in various lengths.

8" version: 4.800 theoretical lumen 12" version: 8.000 theoretical lumen 22" version: 15.000 theoretical lumen 32" version: 24.000 theoretical lumen 42" version: 32.000 theoretical lumen.

The dual-color position-light gives you the possibility to change between white and yellow positions-light as you feel like it so that it fits your vehicle.

The combo-light takes the best of a "spot-" and "flood" light bar. On each side, there are flood lenses, and in the center, spot lenses. This way you have a good combination of the broad light spreading from the sides and the focused light in the center.

The lens glass is produced in polycarbonate and the lamp housing is made of powder-coated aluminum to achieve a sleek design and good cooling for the LEDs.

There are brackets included for mounting and also a pre-mounted 4-pin DT plug, which makes the installation much easier.

• Black: Minus / -

• Red: High-beam

• White: White position-light

• Yellow: Yellow position-light

E-approvements: ECE R112, R7, R10, CE

Ref.: 809179, 809180, 809181, 809182, 809183

Buy online at:

www.matronics.eu/24607011



DR 12" - 45W

SKU 24607011

LEDs: 20

Voltage: 10-40V DC Consumption: 45W

Lumen theoretical: 8000lm Lumen effective: 3294lm

Reference: 45 Kelvin: 6000K

Operating temperature: – 30° C to + 65° C

Dimensions: 71,6 x 76 x 307mm



DR 32" - 143W

SKU 24607013 Voltage: 10-40V DC Consumption: 143W

Lumen theoretical: 24000lm Lumen effective: 8792lm

Reference: 50 Kelvin: 6000K

Operating temperature: – 20°C to +45°C Dimensions: 71,6 x 76 x 817mm



DR 22" - 91W

SKU 24607012 LEDs: 40

Voltage: 10-40V DC

Consumption: 91W

Lumen theoretical: 16000lm Lumen effective: 6316lm

Reference: 45 Kelvin: 6000K

Operating temperature: - 30°C to +65°C

Dimensions: 71,6 x 76 x 562mm

Product pictures







