

Prostroke – HAO hideaway

Powerful LED lights for vehicles. Not road-approved. Sync capable with 19 strobe programs.

Hideaway Type 0 - Powerful LED light sources that can be connected to both 12V and 24V, and are designed to be integrated into existing lights on cars, trucks, and motorcycles. The two robust 3W/5W LEDs provide a wide light beam that spreads throughout the fixture.

The LED light source is installed in a 12mm hole and secured with double-sided tape along its edge.

The LED features a strong strobe light with the capability to switch between 19 different programs using the included controller. It can be synchronized with other connected Prostroke LED devices.

Please be advised that this light source is NOT ECE R65 approved, only R10 (EMC), and therefore CANNOT be used on public roads or highways.

Further information is available under downloads, where you can access the product datasheet detailing the various flash patterns and programs. Although the datasheet incorrectly states R65 approval, this is only for information on the flash patterns and the general setup of the LED light source.

Connection

Connecting the strobe light is straightforward as outlined below.

- White = Synchronization with other Prostroke devices
- Red = Warning light positive (12V-24V)
- Black = Ground / Negative
- Yellow = Flash pattern / program on negative.

Flash Patterns

Pulsing the yellow wire to black (ground / negative) for less than 1 second switches between 26 different flash patterns / programs.

By pulsing between 1-3 seconds, you switch to the previous flash pattern / program.

Pulsing for more than 5 seconds will turn off the flash pattern / program. Reconnecting the LED to power will resume the last selected flash pattern / program.

Buy online at:

www.matronics.eu/731100A

Yellow

SKU 731100A

Hole-size: 12mm

LEDs: 2 x 3W/5W

Voltage: 12-24V

Flash pattern: 19

Temperatures: -30 to +60

Dimensions: Ø25 x 32mm

White

SKU 731100W

Hole-size: 12mm

LEDs: 2 x 3W/5W

Voltage: 12-24V

Flash pattern: 19

Temperatures: -30 to +60

Dimensions: Ø25 x 32mm

Red

SKU 731100R

Hole-size: 12mm

LEDs: 2 x 3W/5W

Voltage: 12-24V

Flash pattern: 19

Temperatures: -30 to +60

Dimensions: Ø25 x 32mm