

## Meanwell transformer for DIN rail

Compact transformers for mounting on DIN rail, that can be used for many purposes. For enclosures and panels.



Compact transformers for mounting on DIN rail, that can be used for many purposes. The transformer is built in to an enclosure or electrical panel, where they can be used for powering low voltage units, for example controllers, low voltage lighting etc. We have 12Vdc and 24Vdc versions.

They are protected against overvoltage, short circuit and overload.

Calibrating the output voltage can be done by adjusting the potentiometer in the front. A LED indicator shows when the unit is on.

The units have standard DIN size, where 15W is 1U, 30W is 2U etc.

Buy online at:

[www.matronics.eu/503621](http://www.matronics.eu/503621)

### Specifications

Protection Over/Under-voltage, short circuit



#### 12V DC, 15W

SKU 503620

Output-voltage: 10.8 - 13.8V

Output-power: 15W

Output-current: 0 - 1.25A

Operating temperature: -30 to +70 degree

Dimensions: 58,4 x 90 x 17,5mm



#### 12V DC, 24W

SKU 503621

Output-voltage: 10.8 - 13.8V

Output-power: 24W

Output-current: 0 - 2A

Operating temperature: -30 to +70 degree

Dimensions: 58,4 x 90 x 35mm



#### 12V DC, 54W

SKU 503622

Output-voltage: 10.8 - 13.8V

Output-power: 54W

Output-current: 0 - 4.5A

Operating temperature: -30 to +70 degree

Dimensions: 54,5 x 90 x 52,5mm



#### 12V DC, 90W

SKU 503623

Output-voltage: 12 - 13V

Output-power: 85W

Output-current: 0 - 7.5A

Operating temperature: -30 to +70 degree

Dimensions: 54,5 x 90 x 70mm



#### 24V DC, 15W

SKU 504620

Output-voltage: 21.6 - 29V

Output-power: 15W

Output-current: 0 - 0.63A

Operating temperature: -30 to +70 degree



#### 24V DC, 36W

SKU 504621

Output-voltage: 21.6 - 29V

Output-power: 30W

Output-current: 0 - 1.5A

Operating temperature: -30 to +70 degree



#### 24V DC, 60W

SKU 504622

Output-voltage: 21.6 - 29V

Output-power: 60W

Output-current: 0 - 2.5A

Operating temperature: -30 to +70 degree



#### 24V DC, 100.8W

SKU 504623

Output-voltage: 24 - 25.5V

Output-power: 100,8W

Output-current: 0 - 4.2A

Operating temperature: -30 to +70 degree

Product pictures

