

Prostroke Hideaway - HA3, R65

Strong LED warning strobe for surface mounting. The 4 bright LEDs creates a wide bright light.



Hideaway type 3 - Powerful LED warning light that can be connected to both 12V and 24V. It allows the LED warning light to be used for many different vehicles such as car, truck and MC.

The LED lamp is made of aluminum, which makes them very robust against harsh weighing conditions. The LED lamp is intended for flat-recess / surface mounting. The LED lamp is mounted in a 25mm hole, or in the included angle bracket.

The LED's 4 LEDs have a powerful yellow strobe light, where it is possible to switch between 26 different programs that can be synchronized with other connected Prostrobe LED lamps.

The LED lamp is ECE R65 approved, and can legally be used throughout Europe and be used on public roads and highways.

You can find further information under downloads, where you can download our datasheet o the product, that has more information regarding the diffent blink patterns / programs.

Dual or single

The single model only has one emitter, dual has two. They have different wire lengths:

Single: 180cm wire

Dual: Emitter 1 has 95cm, emitter 2 has 185cm

The controller itself has 115cm wire on the input, 15cm on the output(s)

Connection

The strobelight connected quite easily as shown below.

- White = Synchronization between other Prostrobe units
- Red = Plus warning light (12V-24V)
- Black = Minus
- Yellow = Blink pattern / programs at minus.

Blink pattern

When you pulse the yellow wire on black (minus) for less than 1 second, you switch between the 26 different flash patterns / programs. The dual model can do alternate flashing between emitter 1 and 2 in some programs.

In pulse between 1-3 seconds, you switch to the previous flash pattern / program.

If the pulse is more than 5 seconds, you turn off the flash pattern / program. If the LED lamp is switched on again, it will continue in the previously selected flash pattern / program.

Reference : 500851, AXIXTECH UR03 F13

Buy online at:

www.matronics.eu/731103A

Specifications

Voltage	12V - 24V
Temperature	-30 to 60 grader
Certificates	R65, R10 (EMC)
Flash patterns	26
LEDs	4 x 5W



Yellow, Single

SKU 731103A

Dimensions: 40 x Ø27mm



Blue, Single

SKU 731103B

Dimensions: 40 x Ø27mm



Blue, Double

SKU 731103DB

Dimensions: 40 x Ø27mm

Product pictures

