

Black-series SLIM LED Light Bar, E-approved, IO-30V

Slim LED lightbar with E-approval and a powerful spot-light. With "hidden" LED's for an anonymous look. Available in multi able lengths.



E-approved Slim "2.0" LED with a single LED line and a powerful spot-light, that is designed in a nice and slim black housing. With "hidden" LED's that gives an anonymous look and discreet look with the dark background. The LED lightbar has a focused and long light beam - perfect for spotlight.

Spot lights give a focused and high beam.

Combo model takes the best of flood and spot. On each side sit flood lenses and in the center - spot lenses. This way you have a good combination of the broad light spreading from the sides and the focused light in the center.

Flood provides a diffused and shorter light beam.

The LED lightbar is produced in an aluminum-housing with a glossy black finish. The result is a light and slim design with optimal cooling for the LEDs. The front glass is polycarbonate, which has a very high tensile strength. The lightbar comes with a cable mounted to a waterproof connector.

Assembly:

The light bar is very easy to install with the included pins, washers, bolts and nuts. The legs are mounted at a suitable distance, after that the bolts are clamped into the side.

matronics 

Buy online at www.matronics.eu/24606223

Product overview

Combo, 25cm (45W) 7 PC. LEFT



SKU 24606223
LEDs: 9 x Osram CSHP
Voltage: 9-36V DC
Consumption 12V / 24V: 1,63A / 0,85A
Operating temperature: - 40°C to +60°C
Lumen effective: 1772lm
Lumen, raw: 3780lm
Reference: 25
Kelvin: 5700K
Dimensions: 54.36 x 40 x 246mm

Combo, 52cm (105W)




SKU 24606224
LEDs: 21 x Osram CSHP
Voltage: 9-36V DC
Consumption 12V / 24V: 3,98A / 2,03A
Operating temperature: - 40°C to +60°C
Lumen effective: 3908lm
Lumen, raw: 8820lm
Reference: 50
Kelvin: 5700K
Dimensions: 54.36 x 40 x 522mm

Flood, 52cm (63W)



SKU 24606227
LEDs: 21 x Osram CSHP
Voltage: 9-36V DC
Consumption 12V / 24V: 3,98A / 2,03A
Operating temperature: - 40°C to +60°C
Lumen effective: 3908lm
Lumen, raw: 8820lm
Reference: 50
Kelvin: 5700K
Dimensions: 54.36 x 40 x 522mm

Flood, 82cm (63W)



SKU 24606228
LEDs: 21 x Osram CSHP
Voltage: 9-36V DC
Consumption 12V / 24V: 3,98A / 2,03A
Operating temperature: - 40°C to +60°C
Lumen effective: 3908lm
Lumen, raw: 8820lm
Reference: 50
Kelvin: 5700K
Dimensions: 54.36 x 40 x 829mm

Accessories, Special mounting brackets



SKU 24606391

Accessories, Mounting brackets stainless steel



SKU 24606395

Product pictures

