## 5 pcs. 3 mm LEDs for External I2V

5 waterproof diodes ready for mounting with 1.0 m cable and mounting frames.



5 waterproof diodes ready for mounting with 1.0 m cable and mounting frames. They are typically used for power lighting, license plate lights or endoutline marker lamps, since they have a wide light scattering.

## matronics.11

Buy online at www.matronics.eu/120002

The cable length is 1.0 m.

The mounting hole should be 6,5 mm.

It can also be attached via cable stripes and a stripes-anchor.

### Product overview

### Blue



SKU 120002

Light Scattering: 120 °

Color: Blue

Brightness: 1000mCD Lens type: Diffuse

Operation Voltage: 12V @ 20mA

Wave Length: ~ 470nm

### Red



SKU 120012

Light Scattering: 120 ° Lens type: Clear glass

Color: Red

Brightness: 1000mCD

Operation Voltage: 12V @ 20mA

Wave Length: ~ 470nm

### Green



SKU 120032

Light Scattering: 120 °

Color: Green Lens type: Diffuse Brightness: 1300 mcd Wave Length: ~ 525nm

Operation Voltage: 12V @ 20mA



SKU 120052

Color: White 6500 k

Operation Voltage: 12V @ 20mA

Lens type: Diffuse Brightness: 1000 mcd Light Scattering: 120 °

### Warm-white



SKU 120056

Lens type: Clear glass

Operation Voltage: 12V @ 20mA

Light Scattering: 60 ° Color: Warm white 2700 k Brightness: 6000 mcd

### Yellow



SKU 120022

Brightness: 1000mCD Light Scattering: 120 °

Color: Yellow Lens type: Diffuse Wave Length: ~ 589nm

Operation Voltage: 12V @ 20mA

### Orange



SKU 120042

Operation Voltage: 12V @ 20mA

Brightness: 1000 mcd Lens type: Diffuse Wave Length: ~ 605nm Light Scattering: 120 °

Color: Orange

# Product pictures

